


# JEN-60

## Drawer Notcher



Includes 57mm insert cutter



### Features:

- Designed to notch and drill the underside of a drawer box for mounting undermount drawer slides
- Pneumatic cutter & drill stroke by foot pedal operation
- Cutter stroke and drill speed are adjustable for optimum finish results
- Drill will automatically position for both left and right drawer notches by activating a switch in the fence
- Machine will not cycle unless a drawer is up against the switch for safe operation
- Insert knife cutterhead with solid carbide inserts for optimum finish results and long tool life
- 2-1/4" (57mm) wide cutter allows for a wide range of undermount slides
- Comes with insert cutterhead with inserts and 1/4" (6.3mm) solid carbide drill bit
- Capable of notching up to 220 drawer boxes (both left and right) per hour

### Machine Includes:

- Solid carbide drill bit 1/4" (6.3MM) 118°
- 10" (255mm) x 2-1/4" (57mm) insert cutter head with 70 pcs. (14x14x1.5mm)

### Specifications:

Main cutter motor.....	3 HP
Notch dimensions.....	2-1/4" (57mm) x 0.5" high
Cutter diameter.....	10"
Drill diameter.....	1/4"
Table size.....	49" x 22"
Table height from floor.....	32"
Dust port.....	4" (670 CFM requirement)
Compressed air required.....	90 - 100 PSI
Machine dimensions.....	48" x 37-3/4" x 39-3/4"
Machine weight.....	506 lbs.



**Würth Louis and Company**

**(800) 422-4389 • www.wurthlac.com**

**OPT-OUT INFORMATION:** You may request Würth Louis and Company not to send any future advertisements to a telephone facsimile machine or machines. Failure to comply with such a request in the form prescribed by law, within the shortest time prescribed by law not to exceed 30 days, is unlawful. If you wish to discontinue future fax advertisements from Würth Louis and Company, Please send your request by Email to: [creditdepartment@wurthlac.com](mailto:creditdepartment@wurthlac.com), or by Fax to: 800-944-7494 or by Calling: 800-444-0043 option 2. Your request should specify the telephone numbers or numbers of each telephone facsimile machine to which the request relates.