

Product details

COMPACT CLIP hinge 3/8", 105°, with spring, hinge cup: press-in



Part number	30C258B.06
Item number	07112531
Color / finish	Nickel-plated
Packaging quantity	250
Weight per 10,000 Pcs in kg	806.48
EAN code	9009494511512
UPC code	

Technical attributes

overlay in inches 3/8 opening angle 105 closing mechanism with spring hinge cup assembly press-in plate arm design and it's assembly With integrated BLUMOTION Depth adjustment + 2.3/- 0.6 mm type of height adjustment with cam Height adjustment +/- 2 mm type of side adjustment with cam minimum boring distance 3 hinge cup finish Nickel-plated hinge cup material Steel hinge cup Flange width 57 Flange height 2 Flange height 2 hinge cup depth 11 diameter hinge cup boring 35 distance between borings 45 eccentric location of mounting holes to hinge cup hole 9.5 directional length of dowel 9.5x8.6 mm (overall length 11.4 mm) collision measurement (hinge arm height) 4 reveal 4.8 self closing start (degrees) 30 diameter of mounting holes 8 overlay in	Attribute	Value
closing mechanism with spring hinge cup assembly press-in plate am design and it's assembly Wiraparound hinge version With integrated BLUMOTION Depth adjustment + 2.3/-0.6 mm type of height adjustment with cam Height adjustment +/-2 mm type of side adjustment with cam minimum boring distance 3 maximum boring distance 3 hinge cup finish Nickel-plated hinge up material Steel hinge cup Elange width 57 Flange height 22 Flange height 25 up boring depth 11 du dameter hinge cup boring 35 distance between borings 45 eccentric location of mounting holes to hinge cup hole 9.5 functional length of dowel 9.5 k8 mm (overall length 11.4 mm) collision measurement (hinge arm height) 4 exit 4.8 self closing start (degrees) 30 didnameter of mounting holes 8 s	overlay in inches	3/8
hinge cup assembly press-in plate am design and it's assembly With integrated BLUMOTION hinge version With integrated BLUMOTION Depth adjustment ± 2.3 - 0.6 mm type of height adjustment with cam type of side adjustment with cam type of side adjustment with cam maximum boring distance 2.5 maximum boring distance Nickel-plated hinge cup finish Nickel-plated hinge cup material 57 Flange width 22 Flange height 2.5 hinge cup depth 11 cup boring depth 11 diameter hinge cup boring 35 distance between borings 45 descentric location of mounting holes to hinge cup hole 9.5 functional length of dowl 9.5 collision measurement (hinge arm height) 4 reveal 4.8 self closing start (degrees) 30 diameter of mounting holes 9.5 Side Adjustment 4-1.6 mm type of d	opening angle	105
plate arm design and it's assembly Wirt integrated BLUMOTION binge version With integrated BLUMOTION Depth adjustment *2.3/-0.6 mm type of height adjustment with cam type of side adjustment */-2 mm type of side adjustment with cam minimum boring distance 2.5 maximum boring distance 3 hinge cup finish Nickel-plated hinge cup finish Steel hinge cup Flange width 57 Flange length 2.5 Flange height 1.1 tinge cup depth 1.1 diameter hinge cup boring 35 distance between borings 45 eccentric location of mounting holes to hinge cup hole 9.5 functional length of dowel 9.5x.8 mm (overall length 11.4 mm) cellision measurement (hinge arm height) 14 reveal 8 self closing start (degrees) 30 didanter of mounting holes 8 voerlay in millimeters 9.5 Side Adjustment 9.1.6 mm <tr< td=""><td>closing mechanism</td><td>with spring</td></tr<>	closing mechanism	with spring
hinge version With integrated BLUMOTION Depth adjustment + 2.3/- 0.6 mm type of height adjustment with cam Height adjustment */- 2 mm type of side adjustment with cam minimum boring distance 2.5 maximum boring distance 3 hinge cup finish Nickel-plated hinge cup material Steel hinge cup Flange width 57 Flange length 2.2 Flange height 1.1 cup boring depth 1.1 distance between borings 35 distance between borings 45 eccentric location of mounting holes to hinge cup hole 9.5 functional length of dowl 9.5x8.6 mm (overall length 11.4 mm) collision measurement (hinge arm height) 14 reveal 4.8 self closing start (degrees) 30 diameter of mounting holes 9.5 self closing start (degrees) 30 diameter of mounting holes 9.5 self closing start (degrees) 30 d	hinge cup assembly	press-in
Depth adjustment + 2.3/- 0.6 mm type of height adjustment with cam Height adjustment +/- 2 mm type of side adjustment with cam type of side adjustment with cam type of side adjustment with cam minimum boring distance 3 maximum boring distance 3 hinge cup finish Nickel-plated hinge cup material Steel hinge cup Flange width 57 Flange length 22 Flange length 1 cup depth 11 distance between boring 35 distance between borings 45 distance between borings 45 functional length of dowel 9.5 collision measurement (hinge arm height) 44 reveal 8 self closing start (degrees) 30 diameter of mounting holes 8 vorlay in millimeters 9.5 Side Adjustment +1.6 mm type of depth adjustment with cam	plate arm design and it's assembly	Wraparound
type of height adjustment with cam Height adjustment #/-2 mm type of side adjustment with cam minimum boring distance 2.5 maximum boring distance 3 hinge cup finish Nickel-plated hinge cup material Steel hinge cup Flange width 57 Flange length 22 Flange height 11 cup boring depth 11 diameter hinge cup boring 35 distance between borings 45 eccentric location of mounting holes to hinge cup hole 9.5 functional length of dowel 9.5x8.6 mm (overall length 11.4 mm) collision measurement (hinge arm height) 14 reveal 4.8 self closing start (degrees) 30 diameter of mounting holes 9.5 self closing start (degrees) 30 diameter of mounting holes 9.5 Side Adjustment 4/-1.6 mm type of depth adjustment 4/1.6 mm	hinge version	With integrated BLUMOTION
Height adjustment +/- 2 mm type of side adjustment with cam minimum boring distance 2.5 maximum boring distance 3 hinge cup finish Nickel-plated hinge cup material Steel hinge cup Flange length 57 Flange height 2.5 hinge cup depth 11 cup boring depth 11 diameter hinge cup boring 35 distance between borings 45 eccentric location of mounting holes to hinge cup hole 9.5 collision measurement (hinge arm height) 14 reveal 4.8 self closing start (degrees) 30 diameter of mounting holes 9.5 self closing start (degrees) 30 diameter of mounting holes 9.5 Side Adjustment +/-1.6 mm type of depth adjustment +/-1.6 mm type of depth adjustment 1 piece	Depth adjustment	+ 2.3/- 0.6 mm
type of side adjustment with cam minimum boring distance 2.5 maximum boring distance 3 hinge cup finish Nickel-plated hinge cup material Steel hinge cup Flange width 57 Flange length 2.5 hinge cup depth 11 cup boring depth 11 diameter hinge cup boring 35 distance between borings 45 eccentric location of mounting holes to hinge cup hole 9.5 functional length of dowel 9.5x8.6 mm (overall length 11.4 mm) collision measurement (hinge arm height) 14 reveal 4.8 self closing start (degrees) 30 diameter of mounting holes 8 overlay in millimeters 9.5 Side Adjustment +/-1.6 mm type of depth adjustment with cam item package 1 piece	type of height adjustment	with cam
minimum boring distance 2.5 maximum boring distance 3 hinge cup finish Nickel-plated hinge cup material 57 Flange width 22 Flange length 2.5 hinge cup depth 11 cup boring depth 11 diameter hinge cup boring 35 distance between borings 45 eccentric location of mounting holes to hinge cup hole 9.5 functional length of dowel 9.5x8.6 mm (overall length 11.4 mm) collision measurement (hinge arm height) 14 reveal 4.8 self closing start (degrees) 30 diameter of mounting holes 8 overlay in millimeters 9.5 Side Adjustment +/-1.6 mm type of depth adjustment with cam item package 1 piece	Height adjustment	+/- 2 mm
maximum boring distance 3 hinge cup finish Nickel-plated hinge cup material Steel hinge cup Flange width 57 Flange length 22 Flange height 11 cup depth 11 cup boring depth 11 diameter hinge cup boring 35 distance between borings 45 eccentric location of mounting holes to hinge cup hole 9.5x8.6 mm (overall length 11.4 mm) cullision measurement (hinge arm height) 14 reveal 4.8 self closing start (degrees) 30 diameter of mounting holes 8 overlay in millimeters 9.5 Side Adjustment +/-1.6 mm type of depth adjustment with cam item package 1 piece	type of side adjustment	with cam
hinge cup finish Nickel-plated hinge cup material Steel hinge cup Flange width 57 Flange length 22 Flange height 11 cup boring depth 11 diameter hinge cup boring 35 distance between borings 45 eccentric location of mounting holes to hinge cup hole 9.5 functional length of dowel 9.5x8.6 mm (overall length 11.4 mm) collision measurement (hinge arm height) 14 reveal 4.8 self closing start (degrees) 30 diameter of mounting holes 8 overlay in millimeters 9.5 Side Adjustment +/-1.6 mm type of depth adjustment with cam item package 1 piece	minimum boring distance	2.5
hinge cup material Steel hinge cup Flange width 57 Flange length 22 Flange height 2.5 hinge cup depth 11 cup boring depth 11 diameter hinge cup boring 35 distance between borings 45 eccentric location of mounting holes to hinge cup hole 9.5 functional length of dowel 9.5x8.6 mm (overall length 11.4 mm) collision measurement (hinge arm height) 14 reveal 4.8 self closing start (degrees) 30 diameter of mounting holes 8 overlay in millimeters 9.5 Side Adjustment +/-1.6 mm type of depth adjustment with cam item package 1 piece	maximum boring distance	3
Flange width 57 Flange length 22 Flange height 2.5 hinge cup depth 11 cup boring depth 11 diameter hinge cup boring 35 distance between borings 45 eccentric location of mounting holes to hinge cup hole 9.5 functional length of dowel 9.5x8.6 mm (overall length 11.4 mm) collision measurement (hinge arm height) 14 reveal 4.8 self closing start (degrees) 30 diameter of mounting holes 8 overlay in millimeters 9.5 Side Adjustment +/-1.6 mm type of depth adjustment with cam item package 1 piece	hinge cup finish	Nickel-plated
Flange length 22 Flange height 2.5 hinge cup depth 11 cup boring depth 11 diameter hinge cup boring 35 distance between borings 45 eccentric location of mounting holes to hinge cup hole 9.5 functional length of dowel 9.5x8.6 mm (overall length 11.4 mm) collision measurement (hinge arm height) 14 reveal 4.8 self closing start (degrees) 30 diameter of mounting holes 8 overlay in millimeters 9.5 Side Adjustment +/-1.6 mm type of depth adjustment with cam item package 1 piece	hinge cup material	Steel hinge cup
Flange height 2.5 hinge cup depth 11 cup boring depth 11 diameter hinge cup boring 35 distance between borings 45 eccentric location of mounting holes to hinge cup hole 9.5 functional length of dowel 9.5x8.6 mm (overall length 11.4 mm) collision measurement (hinge arm height) 14 reveal 4.8 self closing start (degrees) 30 diameter of mounting holes 8 overlay in millimeters 9.5 Side Adjustment +/-1.6 mm type of depth adjustment with cam item package 1 piece	Flange width	57
hinge cup depth 11 cup boring depth 11 diameter hinge cup boring 35 distance between borings 45 eccentric location of mounting holes to hinge cup hole 9.5 functional length of dowel 9.5x8.6 mm (overall length 11.4 mm) collision measurement (hinge arm height) 14 reveal 4.8 self closing start (degrees) 30 diameter of mounting holes 8 overlay in millimeters 9.5 Side Adjustment +/-1.6 mm type of depth adjustment with cam item package 1 piece	Flange length	22
cup boring depth diameter hinge cup boring 35 distance between borings 45 eccentric location of mounting holes to hinge cup hole functional length of dowel collision measurement (hinge arm height) reveal self closing start (degrees) diameter of mounting holes overlay in millimeters Side Adjustment type of depth adjustment item package 11 14 14 14 14 14 14 15 16 17 18 18 18 19 19 19 10 11 11 11 11 11 11 11 11 11 11 11 11	Flange height	2.5
diameter hinge cup boring35distance between borings45eccentric location of mounting holes to hinge cup hole9.5functional length of dowel9.5x8.6 mm (overall length 11.4 mm)collision measurement (hinge arm height)14reveal4.8self closing start (degrees)30diameter of mounting holes8overlay in millimeters9.5Side Adjustment+/-1.6 mmtype of depth adjustmentwith camitem package1 piece	hinge cup depth	11
distance between borings eccentric location of mounting holes to hinge cup hole functional length of dowel collision measurement (hinge arm height) reveal self closing start (degrees) diameter of mounting holes overlay in millimeters Side Adjustment type of depth adjustment item package 45 9.5 8 4.8 8 8 8 9.5 8 9.5 Side Adjustment type of depth adjustment item package 45 45 45 45 46 47 48 48 48 48 48 48 49 40 40 41 41 41 41 41 41 41 41	cup boring depth	11
eccentric location of mounting holes to hinge cup hole functional length of dowel collision measurement (hinge arm height) 14 reveal 4.8 self closing start (degrees) 30 diameter of mounting holes overlay in millimeters 9.5 Side Adjustment type of depth adjustment item package 9.5 \$ 50	diameter hinge cup boring	35
functional length of dowel 9.5x8.6 mm (overall length 11.4 mm) collision measurement (hinge arm height) 14 reveal 4.8 self closing start (degrees) 30 diameter of mounting holes 8 overlay in millimeters 9.5 Side Adjustment +/-1.6 mm type of depth adjustment with cam item package 1 piece	distance between borings	45
collision measurement (hinge arm height) reveal 4.8 self closing start (degrees) 30 diameter of mounting holes 8 overlay in millimeters 9.5 Side Adjustment +/-1.6 mm type of depth adjustment with cam item package 1 piece	eccentric location of mounting holes to hinge cup hole	9.5
reveal 4.8 self closing start (degrees) 30 diameter of mounting holes 8 overlay in millimeters 9.5 Side Adjustment +/-1.6 mm type of depth adjustment with cam item package 1 piece	functional length of dowel	9.5x8.6 mm (overall length 11.4 mm)
self closing start (degrees) diameter of mounting holes 8 overlay in millimeters 9.5 Side Adjustment type of depth adjustment item package 30 wth cam 30 wth cam 31 piece	collision measurement (hinge arm height)	14
diameter of mounting holes overlay in millimeters 9.5 Side Adjustment type of depth adjustment item package 8 with cam 1 piece	reveal	4.8
overlay in millimeters 9.5 Side Adjustment +/-1.6 mm type of depth adjustment with cam item package 1 piece	self closing start (degrees)	30
Side Adjustment +/-1.6 mm type of depth adjustment with cam item package 1 piece	diameter of mounting holes	8
type of depth adjustment with cam item package 1 piece	overlay in millimeters	9.5
item package 1 piece	Side Adjustment	+/-1.6 mm
	type of depth adjustment	with cam
packaging industrial packing	item package	1 piece
	packaging	industrial packing