



Metal Lathe PL-1340

Product Images



Short Description

Metal Lathe PL-1340

Additional Information

Stock Number	BA9-1006057
Center Height	6.5
Compound Rest Travel	2.68
Compound Rest Width	3
Cross Slide Travel (In.)	6.29
Cutting Tool Max Section	.625" x .625"
Distance Between Centers (In.)	40"
Input Power	220V 1-Phase
Lead Screw Diameter	0.875
Leadscrew Thread Pitch	8 T.P.I.
Longitudinal Feeds Imperial Qty Speed	32 / .0020" – .5480" / rev.
Longitudinal Feeds Metric Qty Speed	32 / .052 – 13.92 mm / rev.
Model Number	PL-1340
Modular Pitch Threads Range	21 / .2–3 M.P.
Product Lease Price	502
Prop 65	Cancer and Reproductive Harm
Quill Taper	Morse #5
Shipping Dimensions (L x W x H) (In.)	76x40x62
Spindle Bore (In.)	1.5
Spindle Taper with Sleeve	Morse #3
Swing Over Bed (In.)	13"
Swing Over Cross Slide (In.)	7.79"
Swing Through Gap (In.)	18.75"
Table Length (In.)	5.125"
Tailstock Spindle Travel (In.)	4.5"

Taper in Tailstock Spindle	1.65"
Weight (Lbs.)	1630
Width of Bed (In.)	7.375"
Speed (rpm)	70 - 2000 rpm
Threads Diametrical Quality Type (D.P.)	32 / 8-120 D.P.
Threads Imperial Quality Type (T.P.I.)	31 / 4-56 T.P.I.

