



Metal Lathe - PL-1860E

Product Images



Short Description

Metal Lathe - PL-1860E

Additional Information

| | |
|---------------------------------------|------------------------------|
| Stock Number | BA9-1016624 |
| Center Distance (In.) | 60" |
| Input Power | 220V / 3-phase |
| Lead Screw Diameter | 1.125 |
| Leadscrew Thread Pitch | 4 T.P.I. |
| Longitudinal Feed Imp Qty Type | 122 / .0015"-.0913" / rev. |
| Model Number | PL-1860E-1.0 |
| Modular Pitch Threads Range | 21 / .25 to 10 M.P |
| Motor (HP) | 7.5 hp |
| Nose Radius (In.) | D1-8 |
| Number of Spindle Speeds | 25-1800 rpm |
| Product Lease Price | 1092 |
| Prop 65 | Cancer and Reproductive Harm |
| Quill Taper | MT7 |
| Shipping Dimensions (L x W x H) (In.) | 116x45x66 |
| Spindle Bore (In.) | 3.125" |
| Spindle Taper with Sleeve | MT5 |
| Swing Over Bed (In.) | 18" |
| Swing Over Cross Slide (In.) | 10-3/4" |
| Swing Through Gap (In.) | 27.5" |
| Tailstock Spindle Travel (In.) | 6" |
| Weight (Lbs.) | 5650 |
| Width of Bed (In.) | 13-1/8" |
| Compound Rest Travel | 5-1/8" |
| Cross Slide Travel | 10-1/2" |

Threads Diametrical Quality Type (D.P.) 45 / 3-1/2 to 96 D.P

Threads Imperial Quality Type (T.P.I.) 61 / 1-5/8 to 72 T.P.I

