



# 55 Ton Ironworker 3 Phase, 230 Volt, 10" Brake

## Product Images

---



## Short Description

---

55 Ton Ironworker 3 Phase, 230 Volt, 10" Brake

## Additional Information

---

Stock Number	ED9-55233022
Amps	14
Angle Shear Max Capacity 1/2"	4 x 4
Angle Shear Max Capacity 1/4"	4 x 4
Angle Shear Max Capacity 3/8"	3 x 3
Angle Shear Work Height (In.)	39-7/8
Cylinder (In)	2-1/2" Ram
Flat Bar Shear Max Capacity 1"	12
Flat Bar Shear Max Capacity 1/2"	12
Flat Bar Shear Max Capacity 3/4"	14
Flat Bar Shear Max Capacity 3/8"	14
Flat Bar Shear Max Capacity (In.)	3/8 x 14 1/2 x 12 3/4 x 4
Flat Bar Shear Max Round Capacity (In.)	7/8
Flat Bar Shear Max Round (In)	7/8
Flat Bar Shear Max Square Capacity (In.)	7/8
Flat Bar Shear Max Square (In)	7/8
Flat Bar Shear Work Height (In.)	34-1/2
Hydraulic Pump (GPM)	3-1/2
Hydraulic Reservoir (Gal.)	7
Hydraulics (GPM)	3-1/2
Hydraulics (PSI)	2500
Model Number	55233022
Motor (HP)	5 HP, 230/460V, 3Ph
Open Station Open Height (In)	8-1/8
Open Station Shut Height (In)	6-7/8

Open Station Stroke (In)	1-1/4
Open Station Throat Depth (In)	11-3/16
Open Station Work Height (In)	34-1/2
Open Workstation Throat Depth (In.)	11-3/16
Open Workstation Work Height (In.)	34-1/2
Opt. Coper Notcher Work Height (In.)	39-1/2
Optional Coper Notcher Max Capacity (In.)	2 x 4 x 5/16
Optional Coper Notcher Work Height (In.)	39-1/2
Product Dimensions (In.)	36-1/8 x 44-3/8 x 55-1/4
Prop 65	Cancer and Reproductive Harm
Punch Max Capacity (In.)	1-16 diam. In 5/8 mild steel
Punch Open Height (In)	8-1/8
Punch Rating (Tons)	55
Punch Shut Height (In)	6-7/8
Punch Stroke (In.)	1-1/4
Punch Throat Depth (In.)	7-1/2
Punch Work Height (In.)	36-9/16
Rating (Tons)	55
Reservoir (Gal.)	7
Shipping Dimensions (L x W x H) (In.)	45 x 51 x 62
Valve Pressure (PSI)	2750
Weight (Lbs.)	2480
Amps	14

