



55 Ton Ironworker 3 Phase, 230 Volt, PowerLink, Coper Notcher

Product Images



Short Description

55 Ton Ironworker 3 Phase, 230 Volt, PowerLink, Coper Notcher

Additional Information

| | |
|--|-----------------------------|
| Stock Number | ED9-55233512 |
| Amps | 14 |
| Angle Shear Max Capacity 1/4" | 4 x 4 |
| Angle Shear Max Capacity 3/8" | 3 x 3 |
| Angle Shear Work Height (In.) | 39-7/8 |
| Cylinder (In) | 2-1/2" Ram |
| Flat Bar Shear Max Capacity 1" | 12 |
| Flat Bar Shear Max Capacity 3/4" | 4 |
| Flat Bar Shear Max Capacity (In.) | 3/8 x 14, 1/2 x 12, 3/4 x 4 |
| Flat Bar Shear Max Round Capacity (In.) | 7/8 |
| Flat Bar Shear Max Round (In) | 7/8 |
| Flat Bar Shear Max Square Capacity (In.) | 7/8 |
| Flat Bar Shear Max Square (In) | 7/8 |
| Flat Bar Shear Work Height (In.) | 34-1/2 |
| Hydraulic Reservoir (Gal.) | 7 |
| Hydraulics (GPM) | 3-1/2 |
| Hydraulics (PSI) | 2500 |
| Model Number | 55233512 |
| Motor (HP) | 7.5 HP 3 ~ 230V |
| Motor Speed (RPM) | 1725 |
| Open Station Open Height (In) | 8-1/8 |
| Open Station Shut Height (In) | 6-7/8 |
| Open Station Stroke (In) | 1-1/4 |
| Open Station Throat Depth (In) | 11-3/16 |
| Open Station Work Height (In) | 34-1/2 |

| | |
|---------------------------------------|------------------------------|
| Open Workstation Throat Depth (In.) | 11-3/16 |
| Open Workstation Work Height (In.) | 34-1/2 |
| Opt. Coper Notcher Max Capacity (In.) | 2-1/2 x 4 x 5/16 |
| Opt. Coper Notcher Work Height (In.) | 39-1/2 |
| Product Dimensions (In.) | 44-3/8 x 36-1/8 x 55-1/4 |
| Prop 65 | Cancer and Reproductive Harm |
| Punch Max Capacity (In.) | 1-16 diam. In 5/8 mild steel |
| Punch Open Height (In.) | 8-1/8 |
| Punch Rating (Tons) | 55 |
| Punch Shut Height (In.) | 6-7/8 |
| Punch Stroke (In.) | 1-1/4 |
| Punch Throat Depth (In.) | 7-1/2 |
| Punch Work Height (In.) | 36-9/16 |
| Rating (Tons) | 55 |
| Reservoir (Gal.) | 7 |
| Shipping Dimensions (L x W x H) (In.) | 45 x 51 x 62 |
| Valve Pressure (PSI) | 2750 |
| Weight (Lbs.) | 2480 |



