



# 100 Ton Deluxe Ironworker 460V, 3Ph, with PowerLink

## Product Images

---



## Short Description

---

100 Ton Deluxe Ironworker 460V, 3Ph, with PowerLink

Stock Number	ED9-IW100X-3P460-A
Amps	12
Angle Shear Max Capacity 1/2"	6 x 6
Angle Shear Max Capacity (In.)	6 x 6 x 1/2
Angle Shear Work Height (In.)	43-15/16
Coper Notcher Max Capacity (In.)	3 x 6 x 1/2
Coper Notcher Work Height (In.)	42
Flat Bar Shear Max Capacity 1"	10
Flat Bar Shear Max Capacity 1/2"	18
Flat Bar Shear Max Capacity 3/4"	14
Flat Bar Shear Max Capacity (In.)	1/2 x 18, 3/4 x 14, 1 x 10
Flat Bar Shear Max Round Capacity (In.)	1
Flat Bar Shear Max Round (In)	1
Flat Bar Shear Max Square (In)	1
Flat Bar Shear Rating (Tons)	100
Flat Bar Shear Work Height (In.)	37
Gross Weight (Lbs)	5180
Hydraulic Pump (GPM)	24
Hydraulic Reservoir (Gal.)	17
Hydraulics (GPM)	24
Hydraulics (PSI)	3800
Model Number	IW100DX-3P460-AC
Motor Amps	11
Motor (HP)	7.5 HP 3 ~ 460V
<b>Additional Information</b>	
Motor Speed (RPM)	1765
Overall Dimensions (L x W x H) (In.)	56 x 45-1/2 x 63-1/8

Product Dimensions (In.)	56 x 45-1/2 x 63-1/8
Prop 65	Cancer and Reproductive Harm
Punch Max Capacity (In.)	1-1/16 diam. in 1 mild steel
Punch Open Height (In)	8-3/4
Punch Rating (Tons)	100
Punch Shut Height (In)	6-13/16
Punch Stroke (In.)	1-15/16
Punch Work Height (In.)	39-3/8
Rating (Tons)	100
Reservoir (Gal.)	17
Rod Shear Max Round (In)	1-1/2
Rod Shear Max Square (In)	1-1/4
Rod Shear Work Height (In)	54-1/2
Shipping Dimensions (L x W x H) (In.)	60 x 67 x 69
Valve Pressure (PSI)	3800
Weight (Lbs.)	5180

