



EVS-1440B Electronic Variable Speed Bench Lathe, 3HP

Product Images



Short Description

EVS-1440B Electronic Variable Speed Bench Lathe, 3HP, 230V, 3Ph

Additional Information

Stock Number	JT9-311440
Compound Slide Travel (In.)	3-1/2
Cross Slide Travel (In.)	7
Distance Between Centers (In.)	40
Drive	EVS
Gross Weight (Lbs)	1584
Input Power	230V 3ph
Length of Gap (In.)	9-1/2
Max Tool Size (In.)	3/4 x 3/4
Model Number	EVS-1440B
Motor (HP)	3 HP, 230V, 3-Phase
Motor Power (HP)	3
Motor Voltage (V.)	230
Net Weight (Lbs.)	1320
Number of Inch Threads	34.0000
Number of Longitudinal and Cross Feed Rates	25
Number of Metric Threads	34.0000
Number of Spindle Speeds	Variable
Overall Dimensions (L x W x H) (In.)	68.5 x 28.3 x 50
Prewired Voltage (V.)	230
Prop 65	Cancer and Reproductive Harm
Range of Cross Feeds (IPR)	25
Range of Inch Threads (TPI)	2-56
Range of Longitudinal Feeds (IPR)	0.0016-0.0460

Range of Metric Threads	0.5-12
Range of Spindle Speeds (RPM)	40-2000
Shipping Dimensions (L x W x H) (In.)	76 x 30 x 61
Spindle Bore (In.)	1-1/2
Spindle Mount	D1-4
Spindle Taper	Morse #5
Spindle Taper with Sleeve	MT-5
Spindle Thread (In./TPI)	2 - 56
Steady Rest Capacity (In.)	0.23-0.61 Copper Shaft (Standard) 0.20-2.36 Bearing Roller(OP)
Swing Over Bed (In.)	14
Swing Over Cross Slide (In.)	9-1/16
Tailstock Spindle Travel (In.)	6-1/8
Taper in Tailstock Spindle	MT-3
Weight (Lbs.)	1584
Width of Bed (In.)	7.48

