



GH-1440B with Newall NMS300

Product Images



Short Description

GH-1440B with Newall DP500

Additional Information

| | |
|---|--------------------------------|
| Stock Number | JT9-323446 |
| Carriage Travel (In.) | 37-2/5 |
| Compound Slide Travel (In.) | 3-1/2 |
| Cross Slide Travel (In.) | 7 |
| Length of Gap (In.) | 8 |
| Max Tool Size (In.) | 4/5 x 4/5 |
| Model Number | GH-1440B |
| Motor (HP) | 2 HP, 230V, Single Phase |
| Number of Inch Threads | 34.0000 |
| Number of Longitudinal and Cross Feed Rates | 32/32 |
| Number of Metric Threads | 26.0000 |
| Number of Spindle Speeds | 8 |
| Overall Dimensions (L x W x H) (In.) | 76-13/32 x 29-29/32 x 59-13/16 |
| Prop 65 | Cancer and Reproductive Harm |
| Range of Cross Feeds (IPR) | 0.007 -0.0187 |
| Range of Inch Threads (TPI) | 4-56 |
| Range of Longitudinal Feeds (IPR) | 0.002 -0.0548 |
| Range of Metric Threads | 0.4-7 |
| Range of Spindle Speeds (RPM) | 70-1900 |
| Spindle Bore (In.) | 2 |
| Spindle Mount | D1-5 |
| Spindle Taper with Sleeve | MT6 |
| Steady Rest Capacity (In.) | 0.31-2.95 |
| Swing Over Bed (In.) | 14 |

| | |
|--------------------------------|------|
| Swing Over Cross Slide (In.) | 8 |
| Swing Through Gap (In.) | 20 |
| Tailstock Spindle Travel (In.) | 4 |
| Taper in Tailstock Spindle | MT4 |
| Weight (Lbs.) | 1753 |
| Width of Bed (In.) | 7.32 |

