



GHD-20, 20" Gear Head Drill Press 230V, 3Ph

Product Images





Short Description

GHD-20, 20" Gear Head Drill Press 230V, 3Ph

Additional Information

Stock Number	JT9-354020
Base Dimensions (In.)	26 x 18
Base Work Table (In.)	15-1/4 x 13
Column Diameter (In.)	4-1/2
Distance Column to Spindle (In.)	10
Drilling Capacity Cast Iron (In.)	1-1/2
Drilling Capacity Mild Steel (In.)	1-1/4
Drills to Center of Circle (In.)	20
Model Number	GHD-20
Motor (HP)	2 HP (2 Speed) , 230V, 3Ph
Overall Dimensions (L x W x H) (In.)	32 x 24 x 71
Prop 65	Cancer and Reproductive Harm
Quill Diameter (In.)	3
Quill Feed	Manual
Range of Spindle Speeds (RPM)	60, 120, 130, 230, 260, 450, 460, 800, 900, 1,500, 1,600, 3,000
Range of Spindle Speeds (RPM) Spindle Distance to Base (In.)	
	1,600, 3,000
Spindle Distance to Base (In.)	1,600, 3,000 44-15/16
Spindle Distance to Base (In.) Spindle Distance to Table (Max.) (In.)	1,600, 3,000 44-15/16 30-1/2
Spindle Distance to Base (In.) Spindle Distance to Table (Max.) (In.) Spindle Taper (In. x TPI)	1,600, 3,000 44-15/16 30-1/2 MT-3
Spindle Distance to Base (In.) Spindle Distance to Table (Max.) (In.) Spindle Taper (In. x TPI) Spindle Travel (In.)	1,600, 3,000 44-15/16 30-1/2 MT-3
Spindle Distance to Base (In.) Spindle Distance to Table (Max.) (In.) Spindle Taper (In. x TPI) Spindle Travel (In.) Style (Type)	1,600, 3,000 44-15/16 30-1/2 MT-3 5 Geared Head
Spindle Distance to Base (In.) Spindle Distance to Table (Max.) (In.) Spindle Taper (In. x TPI) Spindle Travel (In.) Style (Type) T-Slot Centers (In.)	1,600, 3,000 44-15/16 30-1/2 MT-3 5 Geared Head 9
Spindle Distance to Base (In.) Spindle Distance to Table (Max.) (In.) Spindle Taper (In. x TPI) Spindle Travel (In.) Style (Type) T-Slot Centers (In.) Table Size (L x W) (In.)	1,600, 3,000 44-15/16 30-1/2 MT-3 5 Geared Head 9 21-3/4 x 19-1/2

