



JTM-4VS Mill With 3-Axis ACU-RITE G-2 MILLPWR CNC

Product Images



Short Description

JTM-4VS Mill With 3-Axis ACU-RITE G-2 MILLPWR CNC

Additional Information

| | |
|---|------------------------------|
| Stock Number | JT9-690948 |
| CNC Package | ACU-RITE MILLPWR® G2 |
| Collet Capacity | 1/8 - 7/8 |
| Distance Spindle to Column (Max.) (In.) | 19 |
| Max Distance Spindle to Table (In.) | 17-1/2 |
| Model Number | JTM-4VS CNC G2 |
| Motor (HP) | 3 HP, 230/460V, 3Ph |
| Number of Axis | 3 |
| Overall Dimensions (L x W x H) (In.) | 66 x 63 x 85 |
| Prop 65 | Cancer and Reproductive Harm |
| Quill Diameter (In.) | 3-3/8 |
| Quill Down Feed Rates (IPR) | .0015 - .003 - .006 |
| Range of Spindle Speeds (RPM) | 60 - 4,200 |
| Spindle Taper (In. x TPI) | R-8 |
| Spindle Travel (In.) | 5 |
| Style (Type) | CNC |
| T-Slot Centers (In.) | 2-1/2 |
| Table Cross Travel (In.) | 12 |
| Table Longitudinal Travel (In.) | 34 |
| Table Size (L x W) (In.) | 9 x 49 |
| Travel of Knee (In.) | 14-1/2 |
| Travel of Ram (In.) | 13-3/8 |
| Weight (Lbs.) | 2420 |
| Work Table Weight Capacity (Lbs.) | 660 |

