

1 Identification

- **Product identifier**
 - *Product number* CNC100
 - *Trade name:* **WATER-BASED CLEAR BINDER**
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals srl
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**
Flam. Liq. 4 H227 Combustible liquid. Flam. Liq. 4
Skin Sens. 1 H317 May cause an allergic skin reaction.
- **Label elements**
 - *GHS label elements*
The product is classified and labeled according to the Globally Harmonized System (GHS).
 - *Hazard pictograms*



GHS07

- *Signal word* Warning
- *Hazard-determining components of labeling:*
2-methyl-2H-isothiazol-3-one
- *Hazard statements*
H227 Combustible liquid. Flam. Liq. 4
H317 May cause an allergic skin reaction.
- *Precautionary statements*
 - P210 Keep away from flames and hot surfaces. . No smoking.
 - P261 Avoid breathing dust/fume/gas/mist/vapors/spray
 - P280 Wear protective gloves/protective clothing/eye protection/face protection.
 - P363 Wash contaminated clothing before reuse.
 - P403+P235 Store in a well-ventilated place. Keep cool.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- *NFPA ratings (scale 0 - 4)*



Health = 0
 Fire = 2
 Reactivity = 0

- *HMIS-ratings (scale 0 - 4)*



HEALTH 0 Health = 0
 FIRE 2 Fire = 2
 REACTIVITY 0 Reactivity = 0

Product number CNC100
Trade name: WATER-BASED CLEAR BINDER

(Contd. of page 1)

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· *Description: Mixture: consisting of the following components.*

· **Dangerous components:**

34590-94-8	Dipropylene glycol monomethyl ether Flam. Liq. 4, H227	10-<20%
108-65-6	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	<0.5%
2682-20-4	2-methyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 Skin Corr. 1B, H314; Eye Dam. 1, H318 Skin Sens. 1, H317	≥0.0015-<0.01%
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330 Skin Corr. 1B, H314; Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100) Skin Sens. 1A, H317	<0.00025%

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:**

Do not use a jet water stream as it may scatter and spread fire.

· **Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

(Contd. on page 3)

Product number CNC100
Trade name: WATER-BASED CLEAR BINDER

(Contd. of page 2)

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

· **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· **Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· **Environmental precautions:**

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· **Reference to other sections**

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

34590-94-8	Dipropylene glycol monomethyl ether	150 ppm
577-11-7	docusate sodium	5.7 mg/m
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm

· **PAC-2:**

34590-94-8	Dipropylene glycol monomethyl ether	1700* ppm
577-11-7	docusate sodium	63 mg/m
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm

· **PAC-3:**

34590-94-8	Dipropylene glycol monomethyl ether	9900** ppm
577-11-7	docusate sodium	380 mg/m
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

Product number CNC100
Trade name: WATER-BASED CLEAR BINDER

(Contd. of page 3)

· Conditions for safe storage, including any incompatibilities
· Storage:
· Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

· Information about storage in one common storage facility: Not required.
· Further information about storage conditions: Keep receptacle tightly sealed.
· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.
· Control parameters
· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

34590-94-8 Dipropylene glycol monomethyl ether

PEL Long-term value: 600 mg/m , 100 ppm

Skin

REL Short-term value: 900 mg/m , 150 ppm

Long-term value: 600 mg/m , 100 ppm

Skin

TLV Long-term value: NIC-50 ppm

(Skin)

108-65-6 2-methoxy-1-methylethyl acetate

WEEL Long-term value: 50 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· Exposure controls
· Personal protective equipment:
· General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· Breathing equipment:

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· Protection of hands:


Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product.

(Contd. on page 5)

Product number CNC100**Trade name: WATER-BASED CLEAR BINDER**

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Goggles recommended during refilling.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

- **Form:**

Fluid

- **Color:**

According to product specification

- **Odor:**

Characteristic

- **Odor threshold:**

Not determined.

- **pH-value:**

Mixture is non-polar/aprotic.

- **Change in condition**

- **Melting point/Melting range:**

Undetermined.

- **Boiling point/Boiling range:**

100 °C (212 °F)

- **Flash point:**

75 °C (167 °F)

- **Flammability (solid, gaseous):**

Not applicable.

- **Ignition temperature:**

270 °C (518 °F)

- **Decomposition temperature:**

Not determined.

- **Auto igniting:**

Product is not selfigniting.

- **Danger of explosion:**

Not determined.

- **Explosion limits:**

- **Lower:**

1.1 Vol %

- **Upper:**

14 Vol %

- **Vapor pressure at 20 °C (68 °F):**

0.4 hPa (0.3 mm Hg)

- **Density (+/- 0,03) at 20 °C (68 °F):**

1.055 g/cm (8.804 lbs/gal)

- **Relative density**

Not determined.

- **Vapor density**

Not determined.

- **Evaporation rate**

Not determined.

- **Solubility in / Miscibility with**

- **Water:**

Fully miscible.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

- **Dynamic:**

Not determined.

- **Kinematic at 20 °C (68 °F):**

40 s (ISO 4 mm)

(Contd. on page 6)

Product number CNC100**Trade name: WATER-BASED CLEAR BINDER**

(Contd. of page 5)

· Oxidising properties:	N.A.	
· Solvent content:		
· Water:	69.7 %	
· VOC content:	13.00 %	
	137.1 g/l / 1.14 lb/gal	
· Solids content:	17.3 %	
· Other information (HAPS)		
1330-20-7	xylene	<0.01%
98-82-8	cumene	<0.01%
· Other information	No further relevant information available.	

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

34590-94-8 Dipropylene glycol monomethyl ether

Oral	LD50	5,135 mg/kg (mouse)
Dermal	LD50	19,020 mg/kg (rabbit)

577-11-7 docusate sodium

Oral	LD50	3,001 mg/kg (mouse)
Dermal	LD50	2,525 mg/kg (rabbit)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,532 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 h	35.7 mg/l (mouse)

2682-20-4 2-methyl-2H-isothiazol-3-one

Oral	LD50	200 mg/kg (mouse)
Dermal	LD50	400 mg/kg (mouse)
Inhalative	LC50/4 h	0.53 mg/l (mouse)

· Primary irritant effect:

- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
Irritant

(Contd. on page 7)

Product number CNC100**Trade name: WATER-BASED CLEAR BINDER**

(Contd. of page 6)

May cause an allergic skin reaction.

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

98-82-8	cumene	2B
---------	--------	----

· **NTP (National Toxicology Program)**

98-82-8	cumene	<0.01%
---------	--------	--------

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**· **Aquatic toxicity:****34590-94-8 Dipropylene glycol monomethyl ether**

EC50	970 mg/l (algae) (72 h)
	1,919 mg/l (daphnia) (48 h)
LC50 (96h)	1,001 mg/l (Fish)

577-11-7 docusate sodium

EC50	100 mg/l (algae) (48 h)
	6.6 mg/l (daphnia) (48 h)
LC50 (96h)	17.3 mg/l (Fish)

108-65-6 2-methoxy-1-methylethyl acetate

EC50	1,001 mg/l (algae) (72 h)
	501 mg/l (daphnia) (48 h)
LC50 (96h)	134 mg/l (Fish)

55965-84-9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)

EC50	0.027 mg/l (algae) (72 h)
	0.16 mg/l (daphnia) (48 h)
LC50 (96h)	0.19 mg/l (Fish)

· **Persistence and degradability** No further relevant information available.· **Substances Easily biodegradable**

34590-94-8	Dipropylene glycol monomethyl ether	.
------------	-------------------------------------	---

· **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

· **Additional ecological information:**· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Other adverse effects** No further relevant information available.

US

(Contd. on page 8)

Product number CNC100
Trade name: WATER-BASED CLEAR BINDER

(Contd. of page 7)

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

- Smaller quantities can be disposed of with household waste.

- Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Hand over to hazardous waste disposers.

- Dispose of contents and container in accordance with local state and federal regulations.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- **UN-Number**

- DOT, ADN, IMDG, IATA

- Not applicable

- Note

- Check the viscosity at section 9

- **UN proper shipping name**

- DOT, ADN, IMDG, IATA

- Not applicable

- **Transport hazard class(es)**

- DOT, ADR, ADN, IMDG, IATA

- Class

- Not applicable

- **Packing group**

- DOT, IMDG, IATA

- Not applicable

- **Environmental hazards:**

- Marine pollutant:

- No

- **Special precautions for user**

- Not applicable.

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

- Not applicable.

- **UN "Model Regulation":**

- Not applicable

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Various regulations

- SARA

- Section 355 (extremely hazardous substances):

- None of the ingredients is listed.

- Section 313 (Specific toxic chemical listings) :

95-63-6	1,2,4-trimethylbenzene	<0.1%
1330-20-7	xylene	<0.01%
1344-28-1	aluminium oxide	<0.01%

(Contd. on page 9)

Product number CNC100**Trade name: WATER-BASED CLEAR BINDER**

(Contd. of page 8)

98-82-8	cumene	<0.01%
---------	--------	--------

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

1330-20-7	xylene
98-82-8	cumene

· **Proposition 65**

· **Chemicals known to cause cancer:**

98-82-8	cumene	*	<0.01%
---------	--------	---	--------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

95-63-6	1,2,4-trimethylbenzene	II	<0.1%
1330-20-7	xylene	I	<0.01%
98-82-8	cumene	D, CBD	<0.01%
526-73-8	1,2,3-trimethylbenzene	II	<0.01%

· **TLV (Threshold Limit Value)**

112945-52-5	silicon dioxide	A4
1330-20-7	xylene	A4
1344-28-1	aluminium oxide	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
- **Contact:** See emergency phone
- **Date of preparation / last revision** 08/30/2021 / 50

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 10)

Product number CNC100
Trade name: WATER-BASED CLEAR BINDER

(Contd. of page 9)

LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Flam. Liq. 3: Flammable liquids . Category 3
 Flam. Liq. 4: Flammable liquids . Category 4
 Acute Tox. 3: Acute toxicity . Category 3
 Acute Tox. 2: Acute toxicity . Category 2
 Skin Corr. 1B: Skin corrosion/irritation . Category 1B
 Eye Dam. 1: Serious eye damage/eye irritation . Category 1
 Skin Sens. 1: Skin sensitisation . Category 1
 Skin Sens. 1A: Skin sensitisation . Category 1A
 STOT SE 3: Specific target organ toxicity (single exposure) . Category 3
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard . Category 1
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard . Category 1

• **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site
 INRS Fiche Toxicologique
 IARC International agency for research on cancer

• * **Data compared to the previous version altered.**