

Printing date 07/09/2020

Version number 21

Reviewed on 07/09/2020

1 Identification

· Product identifier · Product number HGA10 · Trade name: WB CLEAR 2K TOPCOAT 80SH · Application of the substance / the mixture For professional use · Details of the supplier of the safety data sheet · Manufacturer/Supplier: IVM Chemicals srl Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441 1.3.2 Importer Name I.C.& S. DISTRIBUTING CO. Address P.O.BOX 10845 LANCASTER. PA USA E-Mail: nelson@ics-company.com · Information department: Environmental Health and safety office hseoffice@ivmchemicals.com · Emergency telephone number: ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585. Emergency phone number : 001 813-248-0585 2 Hazard(s) identification

· Classification of the substance or mixture The product is not classified, according to the Globally Harmonized System (GHS).

· Label elements

- · GHS label elements Not applicable
 - · Hazard pictograms Not applicable
 - · Signal word Not applicable
 - · Hazard statements Not applicable
- · Classification system:
 - · NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)



3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

(Contd. on page 2) US



Reviewed on 07/09/2020

Printing date 07/09/2020

Version number 21

Product number HGA10 Trade name: WB CLEAR 2K TOPCOAT 80SH

· Dangerou	is components:	
34590-94-8	Dipropylene glycol monomethyl ether	1-<5%
	Flam. Liq. 4, H227	
111-76-2	2-butoxyethanol	1-2.49%
	Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319 Flam. Liq. 4, H227	
57-55-6	propane-1,2-diol	0.5-1%
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)	≥0.00025-<0.0015%
	Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330	
	 Skin Corr. 1B, H314; Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100) Skin Sens. 1A, H317 	

4 First-aid measures

· Description of first aid measures

- · General information:
- No special measures required.

personal protective equipment for first aid responders is recommended. (please see section 8)

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
 - · Most important symptoms and effects, both acute and delayed
 - For symptoms and effects caused by substances, refer to Section 11.
 - · Indication of any immediate medical attention and special treatment needed
 - No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
 - · Suitable extinguishing agents: Use fire fighting measures that suit the environment.

· For safety reasons unsuitable extinguishing agents:

- Do not use a jet water stream as it may scatter and spread fire.
- · Special hazards arising from the substance or mixture

In case of fire, the following can be released: Nitrogen oxides (NOx) Carbon monoxide (CO)

Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment: No special measures required.

(Contd. on page 3)

US



Printing date 07/09/2020

Version number 21

Reviewed on 07/09/2020

Product number HGA10 Trade name: WB CLEAR 2K TOPCOAT 80SH

(Contd. of page 2)

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Not required.

- · Environmental precautions:
- Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

• Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to Section 13.

- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.
- Protective Action Criteria for Chemicals

· PAC-1:				
34590-94-8 Dipropylene glycol monomethyl ether				
111-76-2	2-butoxyethanol	60 ppm		
25265-77-4	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	13 mg/m³		
57-55-6	propane-1,2-diol	30 mg/m ³		
108-01-0	2-dimethylaminoethanol	3.7 ppm		
· PAC-2:				
34590-94-8	Dipropylene glycol monomethyl ether	1700* ppm		
111-76-2	2-butoxyethanol	120 ppm		
25265-77-4	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	140 mg/m ³		
57-55-6	propane-1,2-diol	1,300 mg/m ³		
108-01-0	108-01-0 2-dimethylaminoethanol 4			
· PAC-3:	· PAC-3:			
34590-94-8	Dipropylene glycol monomethyl ether	9900** ppm		
111-76-2	2-butoxyethanol	700 ppm		
25265-77-4	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	840 mg/m ³		
57-55-6	propane-1,2-diol	7,900 mg/m ³		
108-01-0	2-dimethylaminoethanol	72 ppm		

7 Handling and storage

· Handling:

- · Precautions for safe handling No special measures required.
- · Information about protection against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

- · Storage:
 - Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date , it means that the product must be used within 8 months.

- Take on temperature greater than 5 ° C
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.

(Contd. on page 4)

US



Reviewed on 07/09/2020

Printing date 07/09/2020

Version number 21

Product number HGA10 Trade name: WB CLEAR 2K TOPCOAT 80SH

(Contd. of page 3)

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

- · Control parameters
 - Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

34590	-94-8 Dipropylene glycol monomethyl ether		
PEL	Long-term value: 600 mg/m³, 100 ppm Skin		
REL	Short-term value: 900 mg/m³, 150 ppm Long-term value: 600 mg/m³, 100 ppm Skin		
TLV	Short-term value: NIC-606 (909) mg/m³, NIC-100 (150) ppm Long-term value: NIC-303 (606) mg/m³, NIC-50 (100) ppm (Skin)		
111-76	6-2 2-butoxyethanol		
PEL	Long-term value: 240 mg/m³, 50 ppm Skin		
REL	Long-term value: 24 mg/m³, 5 ppm Skin		
TLV	Long-term value: 97 mg/m³, 20 ppm BEI		
57-55-	6 propane-1,2-diol		
WEEL	Long-term value: 10 mg/m ³		
	· Ingredients with biological limit values:		
111-76	6-2 2-butoxyethanol		
BEI 2	00 mg/g creatinine		
	Medium: urine		
	Time: end of shift		
	Parameter: Butoxyacetic acid with hydrolysis		
•.	Additional information: The lists that were valid during the creation were used as basis.		

· Exposure controls

· Personal protective equipment:

- General protective and hygienic measures:
- The usual precautionary measures for handling chemicals should be followed.
- · Breathing equipment: Not required.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

US



Reviewed on 07/09/2020

Printing date 07/09/2020

Version number 21

Product number HGA10

Trade name: WB CLEAR 2K TOPCOAT 80SH

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

nformation on basic physical and o	chemical properties
· General Information	
· Appearance:	
· Form:	Fluid
· Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
 Melting point/Melting range: 	Undetermined.
 Boiling point/Boiling range: 	100 °C (212 °F)
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	240 °C (464 °F)
• Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
• Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
· Lower:	1.1 Vol %
· Upper:	14 Vol %
· Vapor pressure at 20 °C (68 °F):	1.2 hPa (0.9 mm Hg)
• Density (+/- 0,03) at 20 °C (68 °F):	1.026 g/cm³ (8.562 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
• Water:	Fully miscible.
· Partition coefficient (n-octanol/water	-
· Viscosity:	
· Dynamic:	Not determined.
• <i>Kinematic at 20</i> • <i>C</i> (68 • <i>F</i>):	60 s (ISO 6 mm)
• Oxidising properties:	N.A.
· Solvent content:	
· Solvent content: · Water:	64.1 %
· VOC content:	4.28 %
· · · · · · · · · · · · · · · · · · ·	4.20 % 43.9 g/l / 0.37 lb/gal
· Solids content:	31.6 %

ivm Chemicals

Safety Data Sheet acc. to OSHA HCS

Reviewed on 07/09/2020

Printing date 07/09/2020

Version number 21

Product number HGA10 Trade name: WB CLEAR 2K TOPCOAT 80SH

(Contd. of page 5)

- · Other information (HAPS)
- None of the ingredients is listed.
- · Other information

No further relevant information available.

10 Stability and reactivity

· Reactivity typical of the product as indicated in the data sheet

- Chemical stability The product is stable in normal conditions of storage and use recommended • Thermal decomposition / conditions to be avoided:
- No decomposition if used and stored according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

34590-94-8 Dipropylene glycol monomethyl ether

34390-94-	opipiopy	iene grycor monometryr etner
Oral	LD50	5,135 mg/kg (mouse)
Dermal	LD50	19,020 mg/kg (rabbit)
111-76-2 2-butoxyethanol		
Oral	LD50	1,480 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rab)
57-55-6 propane-1,2-diol		
Oral	LD50	20,000 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (mouse)
108-01-0 2-dimethylaminoethanol		
Oral	LD50	1,183 mg/kg (mouse)
Dermal	LD50	1,219 mg/kg (rabbit)
Inhalative	LC50/4 h	6.1 mg/l (mouse)

· Primary irritant effect:

• on the skin: No irritant effect.

· on the eye: No irritating effect.

Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

Contains a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1), 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Safety data sheet available on request.

(Contd. on page 7)

US



Reviewed on 07/09/2020

Printing date 07/09/2020

Version number 21

Product number HGA10 Trade name: WB CLEAR 2K TOPCOAT 80SH

(Contd. of page 6)

- US

· Carcinogenic categories

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 ECOI	odica	l inform	ation
	- grou		auon

• Aquatic t	oxicity:
-	Dipropylene glycol monomethyl ether
EC50	970 mg/l (algae) (72 h)
	1,919 mg/l (daphnia) (48 h)
LC50 (96h)	1,001 mg/l (Fish)
111-76-2 2-	butoxyethanol
EC50	101 mg/l (daphnia) (24 h)
LC50 (96h)	101 mg/l (Fish)
57-55-6 pro	pane-1,2-diol
EC50	19,000 mg/l (algae) (48 h)
	18,340 mg/l (daphnia) (48 h)
LC50 (96h)	40,613 mg/l (Fish)
108-01-0 2-	dimethylaminoethanol
EC50	66.1 mg/l (algae) (72 h)
	98.4 mg/l (daphnia) (48 h)
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2- methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)
EC50	0.027 mg/l (algae) (72 h)
	0.16 mg/l (daphnia) (48 h)
LC50 (96h)	0.19 mg/l (Fish)
Persistence	e and degradability No further relevant information available.
	es Easily biodegradable
	Dipropylene glycol monomethyl ether .
111-76-2	2-butoxyethanol .
57-55-6	propane-1,2-diol .
• Bioaccun • Mobility Additional • General	n environmental systems: nulative potential No further relevant information available. in soil No further relevant information available. ecological information: notes: azard class 1 (Self-assessment): slightly hazardous for water
	Here we did to do not an internet successful to a fift to me a do not successful to the
	allow undiluted product or large quantities of it to reach ground water, water course of system

coatings & polymers technologies

Safety Data Sheet acc. to OSHA HCS

Version number 21

Reviewed on 07/09/2020

Product number HGA10

Printing date 07/09/2020

Trade name: WB CLEAR 2K TOPCOAT 80SH

· Other adverse effects No further relevant information available.

(Contd. of page 7)

US

13 Disposal considerations

· Waste treatment methods

- · Recommendation:
 - Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
 - Recommendation: Disposal must be made according to official regulations.
 - · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number		
· DOT, ADN, IMDG, IATA	Not applicable	
UN proper shipping name		
· DOT, ADN, IMDG, IATA	Not applicable	
Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA · Class	Not applicable	
Packing group		
· DOT, IMDĠ, IATA	Not applicable	
Environmental hazards:		
· Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex	all of	
MARPOL73/78 and the IBC Code	Not applicable.	

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

· SARA

· Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings) :	
111-76-2 2-butoxyethanol	1-2.49%
· TSCA (Toxic Substances Control Act):	
All components have the value ACTIVE.	
· Hazardous Air Pollutants	
None of the ingredients is listed.	
(Con	td. on page 9)

NL 1-2.49%

A3



Safety Data Sheet acc. to OSHA HCS

Printing date 07/09/2020

Version number 21

Reviewed on 07/09/2020

Product number HGA10

Trade name: WB CLEAR 2K TOPCOAT 80SH

· Proposition 65	(Contd. of page 8)
· Chemicals known to cause cancer:	
None of the ingredients is listed.	

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

111-76-2 2-butoxyethanol

· TLV (Threshold Limit Value established by ACGIH)

111-76-2 2-butoxyethanol

·NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: IVM Chemicals Srl

· Contact: See emergency phone

· Date of preparation / last revision 07/09/2020 / 20 · Abbreviations and acronvms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 4: Flammable liquids - Category 4 Acute Tox. 3: Acute toxicity - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Acute Tox. 2: Acute toxicity - Category 2 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Skin Sens. 1A: Skin sensitisation - Category 1A Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

(Contd. on page 10)

US



Reviewed on 07/09/2020

Printing date 07/09/2020

Version number 21

Product number HGA10 Trade name: WB CLEAR 2K TOPCOAT 80SH

(Contd. of page 9)

• Sources REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site INRS Fiche Toxicologique IARC International agency for research on cancer •* Data compared to the previous version altered.

US